



Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Purple	54
Panduit	CT-720 CT-920	Purple	P54
Burndy	MY29 Y644M	Purple	15
Celestra	A45	Purple	54

Cat. Nos	Wire Size		Dimension (in.)						Std. Pkg.
	Code	Flex Class G,H,I,K,M	Bolt Size	B	C	R	ID		
DA4014A-250	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/4	0.78	1.06	1.51	0.57	100	
DA4056A-250	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	5/16	0.79	1.06	1.51	0.57	100	
DA4038A-250	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/8	0.86	1.06	1.51	0.57	100	
DA4012A-250	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/2	1.09	1.06	1.51	0.57	100	
DA4058A-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	5/8	1.33	1.02	1.20	0.56	100	
DA4014A-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/4	0.64	1.02	1.20	0.56	100	
DA4056A-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	5/16	0.70	1.02	1.20	0.56	100	
DA4038A-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/8	0.83	1.02	1.20	0.56	100	
DA4034A-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/4	1.52	1.05	1.20	0.56	100	
DA4012A-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/2	1.08	1.02	1.20	0.56	100	
WP4038A-030	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/8	0.80	1.00	1.20	0.56	100	
DA4014A-251	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	1/4	0.78	1.19	1.35	0.65	100	
DA4056A-251	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	5/16	1.01	1.19	1.35	0.65	100	
DA4038A-251	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	3/8	1.01	1.19	1.35	0.65	100	
DA4012A-251	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	1/2	1.12	1.19	1.35	0.65	100	
DA4058A-251	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	5/8	1.33	1.19	1.35	0.65	100	
DA4034A-251	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	3/4	1.52	1.19	1.35	0.65	100	
DA4014A-252	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/4	0.78	1.06	1.23	0.57	100	
DA4056A-252	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	5/16	0.79	1.06	1.23	0.57	100	
DA4038A-252	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/8	0.86	1.06	1.23	0.57	100	
DA4012A-252	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/2	1.09	1.06	1.23	0.57	100	
DA4012A-261	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	1/2	1.08	1.14	1.35	0.64	100	
DA4014A-261	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	1/4	0.64	1.14	1.35	0.64	100	
DA4034A-261	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	3/4	1.52	1.14	1.35	0.64	100	
DA4038A-261	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	3/8	0.83	1.14	1.35	0.64	100	
DA4056A-261	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	5/16	0.70	1.14	1.35	0.64	100	
DA4058A-261	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	5/8	1.33	1.14	1.35	0.64	100	
LA4038A-250	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/8	0.90	1.06	1.87	0.57	100	
LA4038A-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/8	0.93	1.02	1.94	0.56	100	
LA4012A-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/2	1.08	1.02	1.94	0.56	100	
LA4038AP-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/8	0.83	1.02	1.94	0.56	100	
LA4012AP-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/2	1.08	1.02	1.94	0.56	100	
LA4038AP-251	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	3/8	1.01	1.19	2.56	0.65	100	
LA4012AP-251	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	1/2	1.12	1.19	2.56	0.65	100	
LA4038AP-261	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	3/8	0.83	1.14	1.94	0.64	100	
LA4012AP-261	4/0 AWG	550/24 = 222 kcmil 4/0 Weld	1/2	1.08	1.14	1.94	0.64	100	