



**Installation Information**

| Manufacturer | Tools         | Color | Code |
|--------------|---------------|-------|------|
| T&B          | TBM8 TBM12    | Brown | 87   |
| Panduit      | CT-720 CT-920 | Brown | P87  |
| Burndy       | Y35 Y45       | Brown | 20   |
| Celestra     | A45           | Brown | 87   |

| Cat. Nos     | Wire Size |                               | Dimension (in.) |      |      |      |      |     | Std. Pkg. |
|--------------|-----------|-------------------------------|-----------------|------|------|------|------|-----|-----------|
|              | Code      | Flex Class G,H,I,K,M          | Bolt Size       | B    | C    | R    | ID   |     |           |
| DA5112A      | 500kcmil  | 500 Navy                      | 1/2             | 1.25 | 1.61 | 2.04 | 0.88 | 100 |           |
| DA5158A      | 500kcmil  | 500 Navy                      | 5/8             | 1.58 | 1.61 | 2.04 | 0.88 | 100 |           |
| LA5112A      | 500kcmil  | 500 Navy                      | 1/2             | 1.25 | 1.61 | 2.99 | 0.88 | 100 |           |
| LA5158A      | 500kcmil  | 500 Navy                      | 5/8             | 1.58 | 1.61 | 2.99 | 0.88 | 100 |           |
| DA5138A-250  | 500 kcmil | 500 Navy                      | 3/8             | 1.01 | 1.54 | 2.39 | 0.84 | 100 |           |
| DA5112A-250  | 500 kcmil | 500 Navy                      | 1/2             | 1.17 | 1.54 | 2.39 | 0.84 | 100 |           |
| DA5158A-250  | 500 kcmil | 500 Navy                      | 5/8             | 1.38 | 1.54 | 2.39 | 0.84 | 100 |           |
| DA5134A-250  | 500 kcmil | 500 Navy                      | 3/4             | 1.52 | 1.54 | 2.39 | 0.84 | 100 |           |
| DA5178A-250  | 500 kcmil | 500 Navy                      | 7/8             | 1.77 | 1.54 | 2.39 | 0.84 | 100 |           |
| DA5101A-250  | 500 kcmil | 500 Navy                      | 1               | 1.89 | 1.54 | 2.39 | 0.84 | 100 |           |
| DA5158A-260  | 500 kcmil | 500 Navy                      | 5/8             | 1.33 | 1.55 | 1.91 | 0.84 | 100 |           |
| DA5101A-260  | 500 kcmil | 500 Navy                      | 1               | 1.94 | 1.55 | 1.91 | 0.84 | 100 |           |
| DA5138A-260  | 500 kcmil | 500 Navy                      | 3/8             | 0.83 | 1.55 | 1.91 | 0.84 | 100 |           |
| DA5112A-260  | 500 kcmil | 500 Navy                      | 1/2             | 1.08 | 1.55 | 1.91 | 0.84 | 100 |           |
| DA5134A-260  | 500 kcmil | 500 Navy                      | 3/4             | 1.52 | 1.55 | 1.91 | 0.84 | 100 |           |
| DA5178A-260  | 500 kcmil | 500 Navy                      | 7/8             | 1.77 | 1.55 | 1.91 | 0.84 | 100 |           |
| WP5112A-069  | 500 kcmil | 500 Navy                      | 1/2             | 1.12 | 1.55 | 1.91 | 0.84 | 100 |           |
| LA5112A-250  | 500 kcmil | 500 Navy                      | 1/2             | 1.17 | 1.54 | 3.14 | 0.84 | 100 |           |
| LA5158A-250  | 500 kcmil | 500 Navy                      | 5/8             | 1.38 | 1.54 | 3.14 | 0.84 | 100 |           |
| LA5178A-250  | 500 kcmil | 500 Navy                      | 7/8             | 1.77 | 1.54 | 3.14 | 0.84 | 100 |           |
| LA5112A-260  | 500 kcmil | 500 Navy                      | 1/2             | 1.08 | 1.52 | 2.89 | 0.84 | 100 |           |
| LA5158A-260  | 500 kcmil | 500 Navy                      | 5/8             | 1.33 | 1.52 | 2.89 | 0.84 | 100 |           |
| LA5138AP-260 | 500 kcmil | 500 Navy                      | 3/8             | 0.83 | 1.55 | 2.89 | 0.84 | 100 |           |
| LA5112AP-260 | 500 kcmil | 500 Navy                      | 1/2             | 1.08 | 1.55 | 2.89 | 0.84 | 100 |           |
| DA5156A-251  | -         | 535.3 kcmil 1325/24 500 kcmil | 5/16            | 1.89 | 0.26 | 2.12 | 1.03 | 100 |           |
| DA5138A-251  | -         | 535.3 kcmil 1325/24 500 kcmil | 3/8             | 1.89 | 0.26 | 2.12 | 1.03 | 100 |           |
| DA5112A-251  | -         | 535.3 kcmil 1325/24 500 kcmil | 1/2             | 1.89 | 0.26 | 2.12 | 1.03 | 100 |           |
| DA5158A-251  | -         | 535.3 kcmil 1325/24 500 kcmil | 5/8             | 1.89 | 0.26 | 2.12 | 1.03 | 100 |           |
| DA5112A-261  | -         | 535.3 kcmil 1325/24 500 kcmil | 1/2             | 1.08 | 1.84 | 2.09 | 0.98 | 100 |           |
| DA5158A-261  | -         | 535.3 kcmil 1325/24 500 kcmil | 5/8             | 1.33 | 1.84 | 2.09 | 0.98 | 100 |           |
| DA5156A-261  | -         | 535.3 kcmil 1325/24 500 kcmil | 5/16            | 0.70 | 1.84 | 2.09 | 0.98 | 100 |           |
| DA5138A-261  | -         | 535.3 kcmil 1325/24 500 kcmil | 3/8             | 0.83 | 1.84 | 2.09 | 0.98 | 100 |           |