



Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM12 TBM14M	Black	106
Panduit	CT-920 CT-980	Black	P106
Burndy	Y35 Y45	Black	24
Celestra	A45	Black	106

Cat. Nos	Wire Size		Dimension (in.)					Std. Pkg.
	Code	Flex Class G,H,I,K,M	Bolt Size	B	C	R	ID	
DA7558A	750kcmil	1325/24 = 535 kcmil	5/8	1.58	1.94	2.37	1.06	100
LA7512A	750kcmil	1325/24 = 535 kcmil	1/2	1.25	1.94	3.24	1.06	100
LA7558A	750kcmil	1325/24 = 535 kcmil	5/8	1.58	1.94	3.24	1.06	100
DA7558A-260	750 kcmil	1325/24 = 535 kcmil	5/8	1.33	1.91	2.26	1.03	100
DA7578A-260	750 kcmil	1325/24 = 535 kcmil	7/8	1.77	1.91	2.26	1.03	100
DA7541A-260	750 kcmil	1325/24 = 535 kcmil	1 1/4	2.50	1.91	2.26	1.03	100
DA7512A-260	750 kcmil	1325/24 = 535 kcmil	1/2	1.08	1.91	2.26	1.03	100
DA7558A-241	750 kcmil	1600/24 = 646 kcmil	5/8	1.58	1.94	2.37	1.06	100
WP7558A-023	750 kcmil	1325/24 = 535 kcmil	5/8	1.43	1.90	2.26	1.03	100
LA7512A-260	750 kcmil	1325/24 = 535 kcmil	1/2	1.08	1.89	3.72	1.03	100
LA7558A-260	750 kcmil	1325/24 = 535 kcmil	5/8	1.33	1.89	3.72	1.03	100
LA7538AP-260	750 kcmil	1325/24 = 535 kcmil	3/8	0.83	1.91	3.72	1.03	100
LA7512AP-260	750 kcmil	1325/24 = 535 kcmil	1/2	1.08	1.91	3.72	1.03	100
LA7558A-241	750 kcmil	1600/24 = 646 kcmil	5/8	1.58	1.94	3.24	1.06	100