


COMPRESSION CONNECTORS



Cat. Nos	Application for Cable Size			Dimension(mm)									Std. Pkg.
	Stud(Metric)	mm ²	A.W.G Stripped Length(mm)	E	L	T	F	W	d1	d2	D		
DSND2203BS	3	0.5-1.5	20-16	7.5-8.0	10.7	19.3	0.75	16.00	6	1.7	3.2	4.4	100
DSND2235BS	3.5	0.5-1.5	20-16	7.5-8.0	10.7	19.3	0.75	16.00	6	1.7	3.7	4.4	100
DSND2204BS	4	0.5-1.5	20-16	7.5-8.0	10.7	21.3	0.75	17.00	6.8	1.7	4.3	4.4	100
DSND2204LBS	4	0.5-1.5	20-16	7.5-8.0	10.7	21.3	0.75	17.00	8	1.7	4.3	4.4	100
DSND2205BS	5	0.5-1.5	20-16	7.5-8.0	10.7	23.3	0.75	18.00	10	1.7	5.3	4.4	100
DSND2206BS	6	0.5-1.5	20-16	7.5-8.0	10.7	25.9	0.75	20.00	11	1.7	6.4	4.4	100
DSND1603BS	3	1.5-2.5	16-13	7.5-8.0	10.7	19.6	0.8	18.00	5.5	2.3	3.2	5	100
DSND1635BS	3.5	1.5-2.5	16-13	7.5-8.0	10.7	19.6	0.8	16.00	6	2.3	3.7	5	100
DSND1604BS	4	1.5-2.5	16-13	7.5-8.0	10.7	21.6	0.8	17.00	6.8	2.3	4.3	5	100
DSND1604LBS	4	1.5-2.5	16-13	7.5-8.0	10.7	21.6	0.8	17.00	8	2.3	4.3	5	100
DSND1605BS	5	1.5-2.5	16-13	7.5-8.0	10.7	24.6	0.8	19.00	10	2.3	5.3	5	100
DSND1606BS	6	1.5-2.5	16-13	7.5-8.0	10.7	27.1	0.8	21.00	11	2.3	6.4	5	100
DSND1204BS	4	4-6	12-10	8.5-9.0	12.7	23.9	1	21.00	8	3.4	4.3	7	100
DSND1205BS	5	4-6	12-10	8.5-9.0	12.7	26.1	1	22.00	10	3.4	5.3	7	100
DSND1206BS	6	4-6	12-10	8.5-9.0	12.7	27.9	1	23.00	11	3.4	6.4	7	100
DSND1208BS	8	4-6	12-10	8.5-9.0	12.7	32.3	1	26.00	14	3.4	8.4	7	100
DSND1210BS	10	4-6	12-10	8.5-9.0	12.7	35.3	1	28.00	18	3.4	10.5	7	100