


COMPRESSION CONNECTORS



Cat. Nos	Application for Cable Size			Dimension(mm)									Std. Pkg.
	Stud(Metric)	mm <sup>2</sup>	A.W.G Stripped Length(mm)	E	L	T	F	W	d1	d2	D		
SD2232	3	0.5-1.5	22-16	7.5-8.0	10.5	21	0.75	6.50	5.7	1.7	3.3	4.3	100
SD2237S	3.5	0.5-1.5	22-16	7.5-8.0	10.5	21	0.75	6.50	5.7	1.7	3.8	4.3	100
SD2237L	3.5	0.5-1.5	22-16	7.5-8.0	10.5	21	0.75	6.50	6.4	1.7	3.8	4.3	100
SD2204S	4	0.5-1.5	22-16	7.5-8.0	10.5	21	0.75	6.50	6.4	1.7	4.4	4.3	100
SD2204M	4	0.5-1.5	22-16	7.5-8.0	10.5	21	0.75	6.50	7.2	1.7	4.4	4.3	100
SD2237LL	3.5	0.5-1.5	22-16	7.5-8.0	10.5	21	0.75	6.50	7.2	1.7	3.8	4.3	100
SD2204L	4	0.5-1.5	22-16	7.5-8.0	10.5	21	0.75	6.50	8.1	1.7	4.4	4.3	100
SD2205S	5	0.5-1.5	22-16	7.5-8.0	10.5	21	0.75	6.50	8.1	1.7	5.4	4.3	100
SD2205L	5	0.5-1.5	22-16	7.5-8.0	10.5	21	0.75	6.50	9.5	1.7	5.4	4.3	100
SD2206S	6	0.5-1.5	22-16	7.5-8.0	10.5	21	0.75	6.50	9.5	1.7	6.6	4.3	100
SD2206L	6	0.5-1.5	22-16	7.5-8.0	10.5	27	0.75	11.00	12	1.7	6.6	4.3	100
SD1632	3	1.5-2.5	16-14	7.5-8.0	10.5	21	0.8	6.50	5.7	2.3	3.3	4.8	100
SD1637S	3.5	1.5-2.5	16-14	7.5-8.0	10.5	21	0.8	6.50	5.7	2.3	3.8	4.8	100
SD1637L	3.5	1.5-2.5	16-14	7.5-8.0	10.5	21	0.8	6.50	6.4	2.3	3.8	4.8	100
SD1604S	4	1.5-2.5	16-14	7.5-8.0	10.5	21	0.8	6.50	6.4	2.3	4.4	4.8	100
SD1637LL	3.5	1.5-2.5	16-14	7.5-8.0	10.5	21	0.8	6.50	7.2	2.3	3.8	4.8	100
SD1604M	4	1.5-2.5	16-14	7.5-8.0	10.5	21	0.8	6.50	7.2	2.3	4.4	4.8	100
SD1604L	4	1.5-2.5	16-14	7.5-8.0	10.5	21	0.8	6.50	8.1	2.3	4.4	4.8	100
SD1605S	5	1.5-2.5	16-14	7.5-8.0	10.5	21	0.8	6.50	8.1	2.3	5.4	4.8	100
SD1605L	5	1.5-2.5	16-14	7.5-8.0	10.5	21	0.8	6.50	9.3	2.3	5.4	4.8	100
SD1606S	6	1.5-2.5	16-14	7.5-8.0	10.5	21	0.8	6.50	9.3	2.3	6.6	4.8	100
SD1606L	6	1.5-2.5	16-14	7.5-8.0	10.5	27	0.8	11.00	12	2.3	6.6	4.8	100
SD1237	3.5	4-6	12-10	8.5-9.0	13	25.5	1	7.00	8.3	3.4	3.8	6.7	100
SD1204S	4	4-6	12-10	8.5-9.0	13	25.5	1	7.00	8.3	3.4	4.4	6.7	100
SD1204L	4	4-6	12-10	8.5-9.0	13	25.5	1	7.00	9	3.4	4.4	6.7	100
SD1205	5	4-6	12-10	8.5-9.0	13	25.5	1	7.00	9	3.4	5.4	6.7	100
SD1206S	6	4-6	12-10	8.5-9.0	13	25.5	1	7.00	9	3.4	6.6	6.7	100
SD1206L	6	4-6	12-10	8.5-9.0	13	31.5	1	12.00	12	3.4	6.6	6.7	100
SD1208	8	4-6	12-10	8.5-9.0	13	30.5	1	11.50	14	3.4	8.5	6.7	100
SD1237S	3.5	4-6	12-10	8.5-9.0	13	24.4	1	7.50	7.2	3.4	3.8	6.7	100
SD1204SS	4	4-6	12-10	8.5-9.0	13	24.4	1	7.50	7.2	3.4	4.4	6.7	100