


COMPRESSION CONNECTORS



Cat. Nos	Application for Cable Size			Dimension(mm)									Std. Pkg.
	Stud(Metric)	mm <sup>2</sup>	A.W.G Stripped Length(mm)	E	L	T	F	W	d1	d2	D		
SV2232BS	3	0.5-1.5	22-16	6.5-7.0	10	21	0.75	6.50	5.7	1.7	3.3	4.3	100
SV2237SBS	3.5	0.5-1.5	22-16	6.5-7.0	10	21	0.75	6.50	5.7	1.7	3.8	4.3	100
SV2237LBS	3.5	0.5-1.5	22-16	6.5-7.0	10	21	0.75	6.50	6.4	1.7	3.8	4.3	100
SV2204SBS	4	0.5-1.5	22-16	6.5-7.0	10	21	0.75	6.50	6.4	1.7	4.4	4.3	100
SV2204MBS	4	0.5-1.5	22-16	6.5-7.0	10	21	0.75	6.50	7.2	1.7	4.4	4.3	100
SV2237LLBS	3.5	0.5-1.5	22-16	6.5-7.0	10	21	0.75	6.50	7.2	1.7	3.8	4.3	100
SV2204LBS	4	0.5-1.5	22-16	6.5-7.0	10	21	0.75	6.50	8.1	1.7	4.4	4.3	100
SV2205SBS	5	0.5-1.5	22-16	6.5-7.0	10	21	0.75	6.50	8.1	1.7	5.4	4.3	100
SV2205LBS	5	0.5-1.5	22-16	6.5-7.0	10	21	0.75	6.50	9.5	1.7	5.4	4.3	100
SV2206SBS	6	0.5-1.5	22-16	6.5-7.0	10	21	0.75	6.50	9.5	1.7	6.6	4.3	100
SV2206LBS	6	0.5-1.5	22-16	6.5-7.0	10	27	0.75	11.00	12	1.7	6.6	4.3	100
SV1632BS	3	1.5-2.5	16-14	6.5-7.0	10	21	0.8	6.50	5.7	2.3	3.3	4.8	100
SV1637SBS	3.5	1.5-2.5	16-14	6.5-7.0	10	21	0.8	6.50	5.7	2.3	3.8	4.8	100
SV1637LBS	3.5	1.5-2.5	16-14	6.5-7.0	10	21	0.8	6.50	6.4	2.3	3.8	4.8	100
SV1604SBS	4	1.5-2.5	16-14	6.5-7.0	10	21	0.8	6.50	6.4	2.3	4.4	4.8	100
SV1637LLBS	3.5	1.5-2.5	16-14	6.5-7.0	10	21	0.8	6.50	7.2	2.3	3.8	4.8	100
SV1604MBS	4	1.5-2.5	16-14	6.5-7.0	10	21	0.8	6.50	7.2	2.3	4.4	4.8	100
SV1604LBS	4	1.5-2.5	16-14	6.5-7.0	10	21	0.8	6.50	8.1	2.3	4.4	4.8	100
SV1605SBS	5	1.5-2.5	16-14	6.5-7.0	10	21	0.8	6.50	8.1	2.3	5.4	4.8	100
SV1605LBS	5	1.5-2.5	16-14	6.5-7.0	10	21	0.8	6.50	9.3	2.3	5.4	4.8	100
SV1606SBS	6	1.5-2.5	16-14	6.5-7.0	10	21	0.8	6.50	9.3	2.3	6.6	4.8	100
SV1606LBS	6	1.5-2.5	16-14	6.5-7.0	10	27	0.8	11.00	12	2.3	6.6	4.8	100
SV1237BS	3.5	4-6	12-10	7.0-8.0	13	25.5	1	7.00	8.3	3.4	3.8	6.7	100
SV1204SBS	4	4-6	12-10	7.0-8.0	13	25.5	1	7.00	8.3	3.4	4.4	6.7	100
SV1204LBS	4	4-6	12-10	7.0-8.0	13	25.5	1	7.00	9	3.4	4.4	6.7	100
SV1205BS	5	4-6	12-10	7.0-8.0	13	25.5	1	7.00	9	3.4	5.4	6.7	100
SV1206SBS	6	4-6	12-10	7.0-8.0	13	25.5	1	7.00	9	3.4	6.6	6.7	100
SV1206LBS	6	4-6	12-10	7.0-8.0	13	31.5	1	12.00	12	3.4	6.6	6.7	100
SV1208BS	8	4-6	12-10	7.0-8.0	13	30.5	1	11.50	14	3.4	8.5	6.7	100
SV1237SBS	3.5	4-6	12-10	7.0-8.0	13	24.4	1	7.50	7.2	3.4	3.8	6.7	100
SV1204SSBS	4	4-6	12-10	7.0-8.0	13	24.4	1	7.50	7.2	3.4	4.4	6.7	100