


Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Yellow	62
Panduit	CT-720 CT-920	Yellow	P62
Burndy	MY29 Y644M	Yellow	16
Celestra	A45	Yellow	62

Cat. Nos	Wire Size		Dimension (in.)					Std. Pkg.
	Code	Flex Class G,H,I,K,M	Bolt Size	B	C	R	ID	
DA2514F	250 kcmil	250 Navy 262.6 kcmil	1/4	0.65	1.13	1.40	0.63	100
DA2556F	250 kcmil	250 Navy 262.6 kcmil	5/16	0.88	1.13	1.40	0.63	100
DA2538F	250 kcmil	250 Navy 262.6 kcmil	3/8	0.93	1.13	1.40	0.63	100
DA2512F	250 kcmil	250 Navy 262.6 kcmil	1/2	1.25	1.13	1.40	0.63	100
DA2514F-250	250 kcmil	250 Navy 262.6 kcmil	1/4	0.78	1.17	1.60	0.63	100
DA2556F-250	250 kcmil	250 Navy 262.6 kcmil	5/16	0.79	1.17	1.60	0.63	100
DA2538F-250	250 kcmil	250 Navy 262.6 kcmil	3/8	0.86	1.17	1.60	0.63	100
DA2514F-260	250 kcmil	250 Navy 262.6 kcmil	1/4	0.64	1.11	1.41	0.61	100
DA2538F-260	250 kcmil	250 Navy 262.6 kcmil	3/8	0.83	1.11	1.41	0.61	100
DA2556F-260	250 kcmil	250 Navy 262.6 kcmil	5/16	0.70	1.11	1.41	0.61	100
DA2578F-260	250 kcmil	250 Navy 262.6 kcmil	7/8	1.77	1.11	1.41	0.61	100
DA2512F-260	250 kcmil	250 Navy 262.6 kcmil	1/2	1.08	1.11	1.41	0.61	100
DA2514F-251	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	1/4	0.78	1.28	1.38	0.70	100
DA2556F-251	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	5/16	0.82	1.28	1.38	0.70	100
DA2538F-251	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	3/8	1.01	1.28	1.38	0.70	100
DA2512F-251	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	1/2	1.12	1.28	1.38	0.70	100
DA2558F-251	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	5/8	1.33	1.28	1.38	0.70	100
DA2534F-251	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	3/4	1.52	1.28	1.38	0.70	100
DA2514F-252	250 kcmil	250 Navy 262.6 kcmil	1/4	0.78	1.17	1.38	0.63	100
DA2556F-252	250 kcmil	250 Navy 262.6 kcmil	5/16	0.79	1.17	1.38	0.63	100
DA2538F-252	250 kcmil	250 Navy 262.6 kcmil	3/8	0.86	1.17	1.38	0.63	100
DA2512F-252	250 kcmil	250 Navy 262.6 kcmil	1/2	1.09	1.17	1.38	0.63	100
DA2556F-261	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	5/16	0.70	1.20	1.38	0.65	100
DA2538F-261	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	3/8	0.83	1.20	1.38	0.65	100
DA2512F-261	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	1/2	1.08	1.20	1.38	0.65	100
DA2558F-261	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	5/8	1.33	1.20	1.38	0.65	100
DA2534F-261	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	3/4	1.52	1.20	1.38	0.65	100
WP2512F-025	250 kcmil	250 Navy 262.6 kcmil	1/2	1.12	1.20	1.38	0.64	100
WP2538F-079	250 kcmil	250 Navy 262.6 kcmil	3/8	0.99	1.20	1.38	0.64	100
LA2512F	250 kcmil	250 Navy 262.6 kcmil	1/2	1.25	1.13	1.95	0.63	100
LA2512F-250	250 kcmil	250 Navy 262.6 kcmil	1/2	1.09	1.17	1.96	0.63	100
LA2578F-250	250 kcmil	250 Navy 262.6 kcmil	7/8	1.63	1.25	1.96	0.63	100
LA2512F-260	250 kcmil	250 Navy 262.6 kcmil	1/2	1.08	1.11	1.97	0.61	100
LA2538FP-260	250 kcmil	250 Navy 262.6 kcmil	3/8	0.83	1.10	1.97	0.61	100
LA2512FP-260	250 kcmil	250 Navy 262.6 kcmil	1/2	1.08	1.10	1.97	0.61	100
LA2538FP-251	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	3/8	1.01	1.28	2.59	0.70	100
LA2538FP-261	250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	3/8	0.83	1.20	2.35	0.65	100
DA2512F-241	250 kcmil	250 Weld 650/24 = 262 kcmil 259/.0311 703/.0189	1/2	1.25	1.25	1.40	0.70	100
DA2514F-261	250 kcmil	637/24 Class I,K,M	1/4	0.64	1.29	1.41	0.70	100
DA2556F-263	250 kcmil	637/24 Class I,K,M	5/16	0.70	1.29	1.41	0.70	100
DA2538F-263	250 kcmil	637/24 Class I,K,M	3/8	0.83	1.29	1.41	0.70	100



Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Yellow	62
Panduit	CT-720 CT-920	Yellow	P62
Burndy	MY29 Y644M	Yellow	16
Celestra	A45	Yellow	62

Cat. Nos	Wire Size		Dimension (in.)					Std. Pkg.
	Code	Flex Class G,H,I,K,M	Bolt Size	B	C	R	ID	
DA2512F-263	250 kcmil	637/24 Class I,K,M	1/2	1.08	1.29	1.41	0.70	100
DA2558F-263	250 kcmil	637/24 Class I,K,M	5/8	1.33	1.29	1.41	0.70	100
DA2534F-263	250 kcmil	637/24 Class I,K,M	3/4	1.52	1.29	1.41	0.70	100
LA2538FP-263	250 kcmil	637/24 Class I,K,M	3/8	0.83	1.28	2.35	0.70	100